

55-836

1 ft. DC Coax Power Splitter 1 x 2.1 Female inline to 2 x Male 2.1 Inline Male Plugs

Use this cable to share power from a single power supply to two different electronic devices, Color: Black.



92-163

Solderless 3.5mm Stereo Keystone Insert

Single port insert with labeled spring loaded terminals for inserting up to (20) gauge wire, Color: White. For use with Calrad IR receiver, emitter distribution products and mono or stereo audio applications. Wiring for audio (R=Right channel), (L=Left channel), (G=Ground). Wiring for IR Receivers (S=Signal), (+/+12Vdc), (- =Negative\Ground).



30-574

VGA-DVI Stainless Steel Blank Wallplate

Calrads DVI Wall Plates allow you to easily route DVI connections in your home, office or other network-A/V locations. It is a mounting wall plate that will eliminate messy cables and gaping holes, providing you with a clean, good-looking wiring solution. Perfect for use in commercial installations that require VGA-DVI video jacks. Includes mounting hardware. Use Calrad VGA F-F inline female feedthru jack part number 30-587 and DVI F-F inline female feedthru jack part number 30-710.



55-742F-P

6" Panel Mount Adapter SVHS Female to 2 x Female BNC's

Calrads panel mount S-Video to BNC cable adapter converts 4-pin Mini-DIN connectors to BNC connectors (Y and C) for routing into video switchers, distribution amplifiers, and S-video devices that use BNC style connectors.

Nylon round isolation washers included. Attached ID labels indicating luminance and chrominance. Mounts in 1/2" 'D' cut hole.



Plug



Jack




Solderless screw terminals


30-730 (Plug)  
30-731 (Jack)

4 Inch 2.1mm L.E.D Illuminated Solderless Inline DC Coax Power Plug or Jack


Fits into a standard decora wall plate. The connector can be used with the keystone insert (White) or without it. Handles up to 20 AWG cable. Two colored L.E.D's embedded in the body of the molded connector to indicate power polarities and DC + AC voltage. Perfect for CCTV cameras or any other AC/DC power device that requires inline solderless termination.



Indicates DC Power Positive Center



Indicates DC Power Negative Center



Indicates AC power



95-849

Mini Timer Module

Adjustable timer from 1-60 seconds via a pot on board. N.O./N.C. switch trigger. Compact design: 1.2" X 2.16" X 0.62" (30 x 55 x 16 mm) Operating voltage: 12-24 volts AC or DC Current: 1.8mA (stand-by), 75mA (active). Relay output: Form-C (SPDT) via wires Contact rating: 3 Amps @ 24VDC With built-in beeper output (150mA @ 24VDC) Includes double-sided foam tape. Terminal block accepts up to 20 Awg cable.



Illuminated Buttons

95-824 Heavy Duty Sealed Environment Surface Mount Weatherproof Self Contained Access Control Keypad

IEI 232SE Sealed Environment Surface Mounted Weatherproof Stand Alone Access Control / Door Shunt / Timered Flush Mounted Keypad with Expanded Programming Features. Code flexibility: Codes can be 4-8 digits

Features:

Surface Mounted. ( Box Included), Weatherproof, Vandal Resistant, Heavy Duty, 4 Independent Outputs & Timers, Outputs Assignable By Code, On Board 8 Amp Form C Relay, Up to 120 Users, Remote Triggering Input, Front Programming. Lock Release Relay To Operate Locking Mechanisms, Timered Or Non Tiered Alarm Zone Shunting Relay To Bypass Alarm Systems And Allow Doors To Be Opened, Forced Door Alarm Relay To Trigger A Siren, Alarm Zone Or Other Device If A Door Is Opened Without A Valid User ID, Propped Door Relay To Trigger An Alarm If A Door Is Propped Or Held Open Beyond A Specified Time, 12 or 24 Vdc/Vac Operation, 2 relays: 5A @ 28VDC Form "C", N.O./C./N.C., 1A @ 28VDC Form "C", N.O./C./N.C. Print Out Available With Optional Printer Interface. Dimensions: 4-15/16" x 3-1/8" x 2" (125 x 78 x 51 mm), Weight 18 oz. (510 grams).